

SND103 Roller Cleaning Paste

Technical Datasheet

Date: 28/08/2013

Description

A high viscosity paste designed for deep cleaning and ideally suited for colour change applications.

Non gritty and effective at removing all the non soluble roller deposits, SND103 also helps to prevent glazing and stripping with regular use.

Properties

- Non-flammable – Flashpoint >100°C, with pleasant clean odour.
- Deep Cleaning Action with rejuvenation properties helping restore blanket and rollers life.
- Excellent at removing all non soluble deposits.
- Regular use helps prevent glazing and stripping – prolonging roller life.
- Improves print quality through increasing roller efficiency.
- Low VOC <5% and free from petroleum distillates.
- Suitable for all roller types.

Method of Use

- Apply paste evenly across ink roller train to give each roller a thorough coating.
- Allow press to idle for 3 mins.
- Apply a small quantity of water across the ink roller train and run for 1 min.
- APPLY WASHUP BLADE and flush the system through with water.

Storage and Shelf Life

- Store solvents safely within the printing environment to allow them to acclimatize to pressroom conditions – working temperatures will affect evaporation speed of solvents and hence can influence their effectiveness. Consult own company risk assessment and fire risk assessment for guidance on suitable storage containers depending on properties of the chemical.
- If left unopened and kept in the correct conditions this product has a recommended shelf life of 12 months.

Health and Safety

This product is categorized with the following hazardous associations:

GHS05: Corrosion

GHS07: Exclamation Mark

Always wear suitable safety equipment when handling pressroom chemicals. Will not give rise to significant hazard provided good standards of industrial practice are maintained. Consult MSDS for further information.

Available Pack Sizes

1kg buckets with carry handle

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

For any further information please contact the technical department at ECS (Nottingham) LTD