

NT2710

Canvas

Description:

Base fabric: 600D*600D;

Width: 0.914/1.27/1.52m

Features:

1. Light weight, soft, environment friendly, good appearance, no fading under strong light.
2. Good compatibility with different printing machine, stable ink absorption and fast drying ability, strong adhesion.

Applications:

1. Suitable for indoor and outdoor advertising, exhibition display, sports and election activities.
2. The product is mainly suitable for **Solvent, Eco-solvent, HP Latex and UV printing**.

Technical Data:

Testing condition: Indoor temperature $23\pm 2^{\circ}\text{C}$, Relative humidity $50\pm 5\%$.

Test Term	Unit	Test Method	Average
Base Fabric	Diner	GB/T16604	600DX600D
Weight-finished product	g/m ²	GB/T4669	240±20
Tensile strength at MD	N/5cm	GB/T1040	≥1000
Tensile strength at CD	N/5cm	GB/T1040	≥800
Tearing Strength at break MD	N/5cm	GB/T16578	≥40
Tearing Strength at break CD	N/5cm	GB/T16578	≥30
Applicable Temperature	°C		-20~+70
Flame Retardancy			

- All technical data is subject to change without prior notice.

Storage Condition:

All NAR products need to be stored in the original packing and with the original protection materials, preferably stored hermetically and vertically, do not expose to direct sunlight or heat sources. In order to avoid loss of quality, NAR products should also be stored in suitable conditions, that is at a temperature of $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and a relative humidity of $50 \pm 15\%$. Under these conditions, NAR products can be stored up to one year.

Production and Application Environment:

Production environment: temperature of $25 \pm 5^{\circ}\text{C}$, relative humidity of $50\% \pm 10\%$, clean dust-free environment without suspended matter; Please move the materials to the printing environment 24 hours before printing. Printing test before use, Printing ink temperature of $18^{\circ}\text{C} - 28^{\circ}\text{C}$, Equipment preheating temperature of 30°C .

Application environment: temperature of 18°C to 28°C , relative humidity of $50\% \pm 15\%$.

Warranty Condition :

1. One year service life: stored in suitable conditions, preferably use within 6 months.
2. One year prosecution period: from the product manufacture date, no-acceptance for overdue product.

Important Remark:

The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable. Advise to use the same batch. Please evaluate on the project environment in advance to confirm the products suitability.

Application :

NAR
IDEAS FOR SIGN