

# NZ4321

## Dull Polish Window Film

### Description

Film: 80 micron dull polish film  
Adhesive: transparent adhesive  
Liner : 120gsm PEK liner  
width: 1.22m

### Features:

1. Single surface printing, paste on glass, acrylic transparent objects, double-sided visual effect;
2. Good dimensional stability after application.

### Application:

1. Applicable to Glass, indoor and outdoor advertising
2. This product is mainly suitable for various of solvent, eco- solvent, UV ink printing.

### Technical Data:

Testing method: Indoor temperature 23±2°C、Relative humidity 50±5%.

Test term	Unit	Test method	Average
Thickness PVC	Micron	GB/T6672-2001	80±10
Weight-Liner	g/m <sup>2</sup>	GB4669-1995	120±10
Weight -finished product	g/m <sup>2</sup>	GB4669-1995	290±20
Gloss Rate 60°	%	GB8807-88	≥60
Initial Adhesion	N/25mm	FTM 9	≥5
24h, 180° peel	N/25mm	FTM 1	≥9
Dimensional stability MD	mm	FTM 14	≤1.8
Dimensional stability CD	mm	FTM 14	≤1.5
Tensile strength MD	N/25 mm	GB/T1040.1-2006	≥45
Tensile strength CD	N/25 mm	GB/T1040.1-2006	≥35
Construction	°C		20±10°C
Temperature	°C		-20 ~ +70
Applicable Temperature			

\* All technical data is subject to change without prior notice.

### Storage Condition:

All NAR products should be stored in the original packaging with original protective materials. It is recommended to keep them sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. The storage temperature is 25 ± 5 °C and the relative humidity is 50 ± 15%. Under this condition, the shelf life of the product is 1 years.

## Production and Application Environment:

Production environment: NAR products are recommended to be used in the environment with temperature of  $25 \pm 5$  °C, relative humidity of  $50 \pm 10\%$ , clean, dust-free and suspended solids free environment; it is suggested that the products should be transferred from the storage environment to the printing environment 24 hours in advance. Please test the ink before use, as the ink may not be compatible to the equipment.


## Warranty Condition :

1. One year shelf life: stored in suitable conditions, preferably use within six months. Quality range is only for ink adsorption, other physical parameter is only for reference.
2. One year prosecution period: from the product manufacture date, no-acceptance for overdue product.

## Important Remark:

1. The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable. Environment humidity more than 70% in different district will decrease the printing result.
2. This SAV product is with permanent glue and has the possibility of residual gum with different substrate and pasting period. Advise to use the same batch product to joint.

## Application:



NAR  
IDEAS FOR SIGN